



FEATURES

- Full-duplex audio speakerphone
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

XTS 7IP BK WIFI 840CH-0070

TECHNICAL SPECIFICATION

MODELS	XTS 7IP BK WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Colour	Black

ARTICLE / CODE	DESCRIPTION
----------------	-------------






**XTS 7IP BK WIFI
840CH-0070**

Full-touch video intercom for IP360 system, 7" TFT touch screen display, WiFi and Graphical User Interface - black.

Surface mounted monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated WiFi for remote calls on smartphones running the dedicated app. User interface for managing video intercom unctions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes bracket for surface mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.



Accessories

ARTICLE / CODE	DESCRIPTION	
XTS 7SI 840XC-0080	Flush mounting box for XTS 7 entry panels. Plastic flush mounting box with pre-punched holes for passing the cables, complete with mortar guard.	
XTS 5SI 840XC-0090	Flush mounting box for XTS 5 entry panels. Plastic flush mounting box with pre-punched holes for passing the cables, complete with mortar guard.	
XTS 7SIC 840XC-0100	Flush mounting box for plasterboard walls for XTS 7 entry panels. Plastic flush mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
XTS 5SIC 840XC-0110	Flush mounting box for plasterboard walls for XTS 5 entry panels. Plastic flush mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
XTS 7KT 840XC-0120	Desktop stand for XTS 7 entry panels. Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	
XTS 5KT 840XC-0130	Desktop stand for XTS 5 entry panels. Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	