

MTMA/GSM

INTERCOM MODULE FOR GSM SYSTEMS

COMPATIBLE SYSTEMS



TECHNICAL DATA

Dimensions (mm)	85 x 85 x 35
Packaging dimensions (mm)	156 x 57 x 110
Power supply (V)	14 ÷ 24 AC - DC
Consumption in stand-by mode (mA)	50
Max. absorption (mA)	120
Operating temperature (°C)	-25 ÷ +55
Protection rating (IP)	54
Resolution (pixels)	1280 x 720
900 MHz GSM EGSM signal strength	33 dBm
1800 MHz GSM DCS signal strength	30 dBm

Electronic module with techno-polymer body and 2 call buttons with double, blue or white, namecard backlighting. Slot for on-board micro SIM (micro SIM not included). It can manage up to 1000 telephone numbers and remotely opens the gateway via a telephone ring. Featuring a local electric lock control, auxiliary contact (1A, 30V max), 2 inputs for call 1 and 2 (programmable I/O). The front is equipped with LEDs for visual indication of the system status. It allows to adjust the audio volume of the microphone and speaker and the activation time of the electric lock. Manual programming via SMS or from PC through the MINI USB connector on the front. Supplied with antenna and 2 m cable for antenna remote control. To finish off with intercom front panel. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.

FEATURES

- Manages up to 1000 telephone numbers
- 2 call buttons
- 2 on-board controls: electric lock and auxiliary control (1A, 30V max)
- LED pictograms for status alerts: door opening, active communication, call in progress and system busy
- Adjustable speaker, microphone and electric lock
- Dual blue or white backlit name tags with brightness settings
- Water and dust protection rating IP54
- Programmable via SMS or PC software
- MiniUSB front panel for firmware updating and programming.

DIMENSIONS

